

■ Product Information

Common Mode Coil (AC)

Dimensions(mm) W x D x H	Parts Number	Inductance	Rated Current	Detail	Image
17.5 x 12.5 x 17.5	UU9.8V-303	30.0mH	0.10A		
	UU9.8V-203	20.0mH	0.15A		
	UU9.8V-103	10.0mH	0.20A		
	UU9.8V-502	5.0mH	0.33A		
	UU9.8V-302	3.0mH	0.48A		
	UU9.8V-122	1.2mH	0.60A		
	UU9.8V-102	1.0mH	0.80A		
17.5 x 15.5 x 12.5	UU9.8H-303	30.0mH	0.10A		
	UU9.8H-203	20.0mH	0.15A		
	UU9.8H-103	10.0mH	0.20A		
	UU9.8H-502	5.0mH	0.33A		
	UU9.8H-302	3.0mH	0.48A		
	UU9.8H-122	1.2mH	0.60A		
	UU9.8H-102	1.0mH	0.80A		
22.0 x 17.0 x 23.0	FT20V-333	33.0mH	0.20A		
	FT20V-183	18.0mH	0.33A		
	FT20V-103	10.0mH	0.48A		
	FT20V-802	8.0mH	0.60A		
	FT20V-402	4.0mH	0.80A		
	FT20V-122	1.2mH	1.00A		
	FT20V-801	0.8mH	1.30A		
22.0 x 17.0 x 17.5	FT20H-333	33.0mH	0.20A		
	FT20H-183	18.0mH	0.33A		
	FT20H-103	10.0mH	0.48A		
	FT20H-802	8.0mH	0.60A		
	FT20H-402	4.0mH	0.80A		
	FT20H-122	1.2mH	1.00A		
	FT20H-801	0.8mH	1.30A		
25.5 x 19.0 x 30.0	ET24V-703	70.0mH	0.33A		
	ET24V-503	50.0mH	0.48A		
	ET24V-343	34.0mH	0.60A		
	ET24V-203	20.0mH	0.80A		
	ET24V-123	12.0mH	1.00A		
	ET24V-802	8.0mH	1.30A		
	ET24V-552	5.5mH	1.60A		
ET24V-372	3.7mH	2.00A			
25.5 x 25.5 x 21.0	ET24H-703	70.0mH	0.33A		
	ET24H-503	50.0mH	0.48A		
	ET24H-343	34.0mH	0.60A		
	ET24H-203	20.0mH	0.80A		
	ET24H-123	12.0mH	1.00A		
	ET24H-802	8.0mH	1.30A		
	ET24H-552	5.5mH	1.60A		
ET24H-372	3.7mH	2.00A			
31.0 x 22.5 x 40.0	ET28V-903	90.0mH	0.80A		
	ET28V-553	55.0mH	1.00A		
	ET28V-333	33.0mH	1.30A		
	ET28V-213	21.0mH	1.60A		
	ET28V-193	19.0mH	2.00A		
	ET28V-153	15.0mH	2.30A		
	ET28V-103	10.0mH	2.60A		
ET28V-702	7.0mH	3.50A			
30.0 x 30.0 x 24.5	ET28H-903	90.0mH	0.80A		
	ET28H-553	55.0mH	1.00A		
	ET28H-333	33.0mH	1.30A		
	ET28H-213	21.0mH	1.60A		
	ET28H-193	19.0mH	2.00A		
	ET28H-153	15.0mH	2.30A		
	ET28H-103	10.0mH	2.60A		
ET28H-702	7.0mH	3.50A			

※Specifications are subject to change for improvement without notice.